



Delta™ Vest-Style Harness

Model: 1102000

Back D-ring, tongue buckle leg straps (size Universal).

PRODUCT HIGHLIGHTS

- No-tangle design
- Stand-up back D-ring
- Tongue buckle leg straps
- Repel™ webbing
- Built-in lanyard keepers
- Revolver™ vertical torso adjusters
- Impact Indicator
- Protected labels, equipped with i-Safe™

Delta™ harnesses combine a set of “industry-first” advancements, with popular features making them the workhorse of the industry. Today’s Delta™ represents the culmination of more than twenty years of design, research, manufacturing know-how and on-the-job performance. Delta™ harnesses are as tough as the guys who wear them. They feature coated, corrosion-resistant hardware, water-repellant and abrasion-resistant webbing and a build quality that is second to none. A patented triangular design gives Delta™ harnesses a shape of their own, so you can don them quickly and easily. Throw it in the tool-box or in the back of your truck, think you can tangle it? Just pick it up and it’s ready to put on, tangle-free. The Delta™ pad also incorporates a web spreading design, positioning webbing wider apart on shoulder straps to eliminate abrasion on your neck.





Delta™ Construction Style Positioning Harness

Model: 1101655

Back and side D-rings, belt with pad, shoulder pads, tongue buckle leg straps (size Large).

PRODUCT HIGHLIGHTS

- No-tangle design
- Stand-up back D-ring
- Body belt/hip pad with side D-rings
- Tongue buckle leg straps
- Shoulder pads
- Repel™ webbing
- Built-in lanyard keepers
- Revolver™ vertical torso adjusters
- Impact Indicator
- Protected labels, equipped with i-Safe™

Delta™ harnesses combine a set of “industry-first” advancements, with popular features making them the workhorse of the industry. Today’s Delta™ represents the culmination of more than twenty years of design, research, manufacturing know-how and on-the-job performance. Delta™ harnesses are as tough as the guys who wear them. They feature coated, corrosion-resistant hardware, water-repellant and abrasion-resistant webbing and a build quality that is second to none. A patented triangular design gives Delta™ harnesses a shape of their own, so you can don them quickly and easily. Throw it in the tool-box or in the back of your truck, think you can tangle it? Just pick it up and it’s ready to put on, tangle-free. The Delta™ pad also incorporates a web spreading design, positioning webbing wider apart on shoulder straps to eliminate abrasion on your neck.



3M™ Protecta® Comfort Construction Style Positioning Harness 1161205, Black, Medium/Large, 1 EA/Case

3M ID 70804486879, 3M Product Number 1161205

- Easy-link web adapter enables fast and easy attachment of personal self-retracting lifelines and keeps the D-ring available for lanyards, overhead SRLs or rescue devices
- Fixed D-ring reduces the need for readjustment throughout the workday
- Specifically designed for added comfort

3M™ Protecta® Comfort Construction-Style Positioning Harness with an easy-link web adapter, a fixed D-ring to minimize workday readjustment and breathable Back/Hip Padding. Plus, a durable and sturdy belt, Tongue-Buckle Leg Connection, Pass-Through Chest Connection and Back and Side D-rings. Specially designed for added comfort, these harnesses are rated for 420 lbs (190 kg) total working weight.

Hardware features include Tongue-Buckle Leg Connection, Pass-Thru Chest Connection, Parachute Torso Buckle, and Back and Side D-rings. The Back D-ring provides a general fall arrest device connection point and is included on all models of 3M™ Protecta® Comfort Construction-Style Harnesses. Side D-rings located on hips are used for attachment of positioning devices to allow workers use of both hands.

Regulatory and Standards Compliance

3M™ Protecta® Fall Protection Harnesses are designed for a maximum capacity of 420 lbs (190 kg), including the worker's body weight, clothing, tools and other accessories. These fall arrest systems meet the requirements of ANSI Z359.11; and OSHA 1910.140 and 1926.502.



3M™ Protecta® Construction Style Positioning Harness 1161309, Black, Medium/Large, 1 EA/Case

3M ID 70804487653, 3M Product Number 1161309

- Fixed D-ring reduces the need for readjustment throughout the workday
- Specifically designed for added comfort
- Moisture-wicking, breathable back padding with soft edging for added comfort

3M™ Protecta® Construction-Style Positioning Harness with a fixed D-ring to minimize workday readjustment, and breathable Shoulder/Hip Padding. Plus, a durable and sturdy belt, Tongue-Buckle Leg Connection, Pass-Through Chest Connection, and Back and Side D-rings. Specially designed for added comfort and convenience, these harnesses are rated for 420 lbs (190 kg) total working weight.

Hardware features include Tongue-Buckle Leg Connection, Pass-Thru Chest Connection, Parachute Torso Buckle, a Back D-ring, Side D-rings. The Back D-ring provides a general fall arrest device connection point and is included on all models of 3M™ Protecta® Construction-Style Positioning Harnesses. Side D-rings located on hips are used for attachment of positioning devices to allow workers use of both hands.

Regulatory and Standards Compliance

3M™ Protecta® Fall Protection Harnesses are designed for a maximum capacity of 420 lbs (190 kg), including the worker's body weight, clothing, tools and other accessories. These fall arrest systems meet the requirements of ANSI Z359.11; and OSHA 1910.140 and 1926.502.





Fall Protection

3M™ DBI-Sala® ExoFit NEX™ Construction
Harness: Large, 40" - 48" Waist

PART NUMBER 1113142

OR

3M™ DBI-Sala® ExoFit NEX™ Construction
Harness: X-Large, 44" - 52" Waist

PART NUMBER 1113145

This harness wraps around you for the ultimate in no-tangle donning and comfortable security. The shoulder, hip and leg padding is built-in so it can't slip. The tongue buckle leg straps and body belt are easily adjustable. The soft edging moves with you and doesn't rub or chafe for added comfort. The breathable lining guarantees you'll stay dry and comfortable every day. Repel web technology extends harness life by resisting moisture and abrasion. Built-in carrying pouch holds a cell phone or other small items.



3M™ DBI-SALA® ExoFit NEX™ Vest-Style Harness 1113007, Large, 1 EA

3M ID 70007419701, 3M Product Number 1113007

OR

3M™ DBI-SALA® ExoFit NEX™ Vest-Style Harness 1113010, X-Large, 1 EA

3M ID 70007426276, 3M Product Number 1113010

- Duo-Lok™ quick connect chest and leg straps
- Repel™ webbing
- Protective shoulder caps
- Loops for body belt
- Built-in lanyard keepers
- Revolver™ vertical torso adjusters
- Impact Indicator
- Integrated trauma straps
- Built-in reflective materials
- Protected labels, equipped with i-Safe™

Aluminum back D-ring, locking quick connect buckle leg straps, comfort padding

ExoFit NEX™ harnesses are the most advanced harnesses in the industry. They're the culmination of our experience with ExoFit™ and ExoFit™ XP, ongoing research and the incorporation of new materials and innovative features. True to our NEX mission, we manufacture these harnesses using materials that won't add unnecessary weight for ultimate comfort. When speed and efficiency are project requirements, ExoFit NEX™ will provide the freedom and confidence to function at your maximum potential. Finally, ExoFit NEX™ harnesses are designed using materials that last. Get into the best, the ultimate comfort, function and durability harness, ExoFit NEX™.





Elk River

Personal Fall Protection

IRONEAGLE HARNESS L

Item #: 65323

Materials:

Nylon and Polyester webbing

Features:

Quick connect chest, Tongue buckle shoulders and leg straps, Removable tool belt, 5" padded backpad, Padded shoulders, Lanyard parks

D-Rings: 3 1-back, 2-hips

Type Use:

Industrial / Construction / General / Tower

Man Rating:

Man-rated to 400lbs

Classification:



Fall Arrest
Class A



Positioning
Class P

Meets or Exceeds:

OSHA 1926

ANSI Z359.11

CSA Z259.10

