



Where People and Technology  
Make the Difference

Browse Products by:

CONSTRUCTION ▾

PRODUCT ▾

APPLICATION ▾

Home

About Samson ▾

Products/Industries ▾

Resources & Literature ▾

Find A Distributor

Careers

## ARBOR-PLEX



PRODUCT CODE: 346

FIBER (CORE/COVER): POLYPROPYLENE  
- POLYESTER BLEND

SPECIFIC GRAVITY: 1.18

SPLICE: NON SPLICEABLE

Arbor-Plex is a lightweight, high strength 12-strand climbing line, and the most widely used rigging line in the arborist industry. It resists snags and has excellent knot-holding ability. Arbor-Plex works well when wet and is very durable.

ELASTIC ELONGATION:

10% | 20% | 30%  
3.00% | 3.30% | 4.20%

SPECIFICATIONS:

DIAM. (inch)	WEIGHT PER 100 FT. (lbs)	AVG. STRENGTH (lbs)	WORKING LOAD (lbs)	WORKING LOAD (kg)	DIAM. (mm)	WEIGHT PER 100 M (kg)	AVG. STRENGTH (kg)
1/2	6.8	6,000	1,200	540	12	10.1	2,700
5/8	12	9,000	1,800	820	16	17.9	4,100
3/4	16.2	12,000	2,400	1,100	18	24.1	5,400

Specifications are for unspliced strengths.

### PRINT THIS PAGE

Adobe Reader required. Download it for free [here](#).

### APPLICATIONS ▲

- Climbing Line
- Rigging Line

### FEATURES AND BENEFITS ▲

- Durable
- Economical
- No-twist stripe
- Snag resistant
- Works well in wet conditions