



Where People and Technology
Make the Difference

Browse Products by:

CONSTRUCTION ▾

PRODUCT ▾

APPLICATION ▾

Home

About Samson ▾

Products/Industries ▾

Resources & Literature ▾

Find A Distributor

Careers

SSR-100-3

PRODUCT CODE: 200

FIBER (CORE/COVER): ULTRA BLUE
POLYOLEFIN-POLYESTER BLEND

SPECIFIC GRAVITY: 1.18

SPLICE: 3-STRAND CLASS I

SSR-100-3 is a combination fiber 3-strand rope with an excellent wear life and a high strength-to-weight ratio. SSR-100-3 is produced with high-strength, plied-filament polyester surface yarns wrapped over our high-tenacity Ultra Blue fiber. This rope offers the durability of polyester, but with higher strengths than other combination ropes due to the Ultra Blue fiber.

ELASTIC ELONGATION:

-10%	20%	30%
1.60%	3.50%	4.70%

SPECIFICATIONS:

DIAM. (inch)	CIRC. (inch)	WEIGHT PER 100 FT. (lbs)	AVG. STRENGTH (lbs)	MIN. STRENGTH (lbs)	DIAM. (mm)	CIRC. (mm)	WEIGHT PER 100 M (kg)	AVG. STRENGTH (kg)	MIN. STRENGTH (kg)
1/4	3/4	1.4	1,800	1,600	6	18	2.1	820	730
5/16	1	2.4	2,800	2,500	8	24	3.6	1,300	1,100
3/8	1 1/8	3.4	4,100	3,700	9	27	5.1	1,900	1,700
7/16	1 1/4	4.9	5,100	4,600	11	33	7.3	2,300	2,100
1/2	1 1/2	6	6,900	6,200	12	36	8.9	3,100	2,800
9/16	1 3/4	8.5	9,100	8,200	14	42	12.6	4,100	3,700
5/8	2	9.5	10,000	9,000	16	48	14.1	4,500	4,100

Specifications are for spliced strengths.

PRINT THIS PAGE

Adobe Reader required. Download it for free [here](#).

APPLICATIONS ▲

- Block Line
- Hand Line

FEATURES AND BENEFITS ▲

- Durable
- Easy to splice
- Economical
- Hockle resistant